

OPERATING & SAFETY GUIDE

This appliance is only for professional use by a qualified operator



Caterer Gas Barbeque
Product Code 602043

A Full EHA Code of Practice for the "Safe Use of LPG" is available on our website www.allenshire.co.uk
Please go to our Gas Appliances and BBQs catalogue page to download

Care of Gas Griddle

Do not lean over grill while lighting.

In order for the igniter switch to work, please make sure the battery is properly installed.

Instructions for Lighting

1. Make sure the gas burner control valves are switched OFF.
2. Use the separation instructions provided to connect to the LPG cylinder.
3. Once the gas is turned on at the cylinder, to ignite the griddle, push and turn the Ignition Burner knob to MAX.
4. Push and hold electric ignition button until the ignition burner lights.
5. If ignition does NOT occur in 5 seconds, turn the burner controls OFF, wait 5 minutes and repeat the lighting procedure.
6. To ignite remaining burners, turn each burner knob in sequence to the position, starting with the burner closest to the edge
7. Once each burner has ignited, turn knobs to desired setting.

GENERAL SAFETY ADVICE

Allens will have prepared, checked and delivered this appliance to you in accordance with the Code of Practice entitled "Safe Use of LPG: Portable and Transportable Equipment in the Hire Industry" (LPG Code) launched in October 2013 by the Event Hire Association (EHA).

**PLEASE READ THESE INSTRUCTIONS CAREFULLY.
THERE IS A RISK OF INJURY IF YOU DO NOT FOLLOW THE INSTRUCTIONS IN THIS GUIDE.**

These instructions are provided so you can familiarise yourself with proper and safe operation of this appliance but are not a substitute for being conversant with duties as hirer under the LPG Code.

The safe use of hired gas equipment is the sole responsibility of the hirer once the items are collected or arrive on site. Allens staff are not allowed to install equipment on site and you are not permitted to make any alterations to the appliance or its connectors in any way.

If in any doubt please ask an Allen's advisor for advice on 020 8574 9600 or a gas safe engineer conversant with the LPG Code.

Never use the equipment in a poorly ventilated space. Keep all children, animals and bystanders away from the work area. Ensure the floor of the work area is free from trip hazards and non-slip.

Keep a bucket of water nearby to treat burns. Use a CO2 extinguisher in case of fire. Wear suitable clothing, such as an apron, overall and hat. Use kitchen/BBQ gloves to handle utensils. Tie back long hair.

Allow the appliance to cool fully before touching or cleaning.

Instructions in case ignitor fails

- If ignitor does not work, follow match lighting instructions.
1. Place match into match holder (hanging from side panel of griddle). Light match; then light burner by placing match on right or left side of griddle.
 2. Push in and turn far right or far left burner knob to the HI position, depending on match light hole selected. Be sure burner lights and stays lit.
 3. Light adjacent burners in sequence by pushing knobs in and turning to the HI position.

Regulators and valves should make a metal-to-metal gas tight seal or be fitted with a rubber seal. On no account should PTFE tape, thread tape or any other sealant be used to try to secure a gas-tight seal in a leaking connection.