

OPERATING & SAFETY GUIDE

This appliance is only for professional use by a qualified operator



Single Gas Burner Product Code 602009

A Full EHA Code of Practice for the "Safe Use of LPG" is available on our website www.allenshire.co.uk Please go to our Gas Appliances and BBQs catalogue page to download

Never use the equipment in a poorly ventilated space. Keep all children, animals and bystanders away from the work area. Ensure the floor of the work area is free from trip hazards and non-slip.

Keep a bucket of water nearby to treat burns. Use a CO₂ extinguisher in case of fire. Wear suitable clothing, such as an apron, overall and hat. Use kitchen/BBQ gloves to handle utensils. Tie back long hair.

Allow the appliance to cool fully before touching or cleaning.

GENERAL SAFETY ADVICE

Allens will have prepared, checked and delivered this appliance to you in accordance with the Code of Practice entitled "Safe Use of LPG: Portable and Transportable Equipment in the Hire Industry" (LPG Code) launched in October 2013 by the Event Hire Association (EHA).

PLEASE READ THESE INSTRUCTIONS CAREFULLY.
THERE IS A RISK OF INJURY IF YOU DO NOT FOLLOW
THE INSTRUCTIONS IN THIS GUIDE.

These instructions are provided so you can familiarise yourself with proper and safe operation of this appliance but are not a substitute for being conversant with duties as hirer under the LPG Code.

The safe use of hired gas equipment is the sole responsibility of the hirer once the items are collected or arrive on site. Allens staff are not allowed to install equipment on site and you are not permitted to make any alterations to the appliance or its connectors in any way.

If in any doubt please ask an Allens advisor for advice on 020 8574 9600 or a gas safe engineer conversant with the LPG Code.

Care of Single Gas Burner

Protect the surface the burner is sitting on from heat.

There is no flame failure cut off on this item. Do not leave unattended.

Ensure it is sighted in a sheltered area so the flame cannot blow out.

Lighting the Burner

- Turn OFF the appliance before connecting to the gas.
- Use separate instructions provided for connecting the LPG cylinder to this appliance.
- When the gas supply is turned on. Turn on the appliance and apply a lighted match or taper to the gas ring.

Regulators and valves should make a metal-to-metal gas tight seal or be fitted with a rubber seal. On no account should PTFE tape, thread tape or any other sealant be used to try to secure a gas-tight seal in a leaking connection.